



The EDC (*Electronic Demand Control*) range keeps pace with everyday needs, guaranteeing high efficiency and low running costs. The control valve has a built-in water meter to measure the amount of water you use, then it automatically activates a regeneration (if required) at 2am, a time when little, if any, water is being used.

- High flow rates, up to 75–130 lpm at 1 bar press/drop
- 24 volt plug-in transformer for safe operation
- Reliable controller – measures and remembers your daily water consumption
- Low salt and water use – only regenerates when necessary based on your actual water needs
- Easy programming
- 3-year parts and 12-month labour warranty
- Self-adjusting reserve capacity constantly adjusts to your daily needs
- Retains memory, even in the event of a power cut
- Solid-state electronics and a reliable metering system for years of trouble-free operation
- 400 micron injector protection prevents injector blockages and subsequent overflows
- Simple and rugged operation. Proven reliability and technology over many years
- Integral bypass automatically provides water during regeneration process

Model	Dimensions (mm)					Capacity (per regen) @300ppm	Salt Use (per regen)	Technical (all models)	Code
	Vessel c/w Valve			Salt Tank					
	H	W	D	H	Dia				
EDC20	1100	220	410	850	550	3460 litres	3.0 kg	20 – 70 psi	EDC20
EDC30	1100	275	410	850	550	5200 litres	4.8 kg	5 – 45 degrees	EDC30
EDC50	1580	275	410	850	550	8650 litres	8 kg	3 pin 13A socket reqd	EDC50
EDC75	1580	355	450	975	690	13000 litres	12 kg	240v / 24v	EDC75
EDC100	1895	385	480	975	690	17300 litres	16 kg	All units with 1" male connections	EDC100
EDC125	1895	430	525	975	690	21625 litres	20 kg	22mm/28mm x 1" adapters provided	EDC125
EDC75/PF	1623	390	575	975	690	13000 litres	12 kg		EDC75/PF
EDC100/PF	1904	403	575	975	690	17300 litres	16 kg	20–70 psi	EDC100/PF
EDC150/PF	1904	428	575	975	690	25950 litres	23 kg	5–45 degrees	EDC150/PF
EDC200/PF	1952	491	595	1110	875	34600 litres	30 kg	3 pin 13A socket reqd	EDC200/PF
EDC250/PF	1952	555	627	1110	875	43250 litres	38 kg	240v / 24v	EDC250/PF
EDC350/PF	2148	635	667	1110	875	60550 litres	53 kg	All units with 1½" male connections	EDC350/PF
EDC500/PF	2066	786	786	1110	1030	86500 litres	75 kg		EDC500/PF

ProFlow models above are suitable for 1½" and 2" supplies, up to 7.8m³/hr.